

INTREPID SP – High Performance Semi Premium Connection

Intrepid SP is a proven Semi Premium Connection developed to face customer challenges. Intrepid SP allows to combine Drilling with Casing assure high torque resistance. Fully interchangeable with API BUTTRESS connection, casing accessories. Bending capability of the connection is higher than 20° / 100 ft.



AVAILABLE SIZES:

4 ½" & 5 ½"

INTREPID SP FEATURES:

- Fully interchangeable with API BUTTRESS connection, casing accessories
- "Pin-to-shoulder" design
- True ID
- High operational Torque
- Enhanced structural capacity

INTREPID SP MAIN APPLICATIONS:

- Drilling with Casing
- Shale
- Intermediate casing
- Production casing

INTREPID SP

Performance DATA

OD: 4,5 in.

WEIGHT: 15,10 ppf

STEEL GRADE: P110

CONNECTION: INTREPID SP

PIPE BODY PROPERTIES

Nominal OD	4,500 in.	Standard Drift	3,701 in.
Nominal ID	3,826 in.	Nominal Weight	15,10 lb/ft
Wall Thickness	0,337 in.	PBYS	110 ksi
Internal Pressure Capacity	14 420 psi	External Pressure Resistance	14 340 psi

CONNECTION PARAMETERS

Coupling OD	5,000 in.	Bending	20° / 100 ft
Coupling Length	9,055 in.	Minimum Make-up Torque	8 500 ft.lb
Make-up loss	3,937 in.	Optimum Make-up Torque	9 220 ft.lb
Compression efficiency	485 klb	Maximum Make-up Torque	10 000 ft.lb
Tension efficiency	485 klb	Operational torque	14 750 ft.lb

CONTACTS

Daniel Valk
Sales director
 Cell: +1 281 236 2949

North American Interpipe
 1800 West Loop South, Site 1350,
 Houston, Texas, 77027, USA
 Phone: +1 713 333 0333
 Fax: +1 713 333 0330
www.na.interpipe.biz
www.interpipe.biz